



Rick Scott
Governor

H. Frank Farmer, Jr., M.D., Ph.D., FACP
State Surgeon General

**APPLICATION FOR
RESURFACING OF COMMERCIAL POOL/SPA**

Name of Pool or Spa: _____

Address: _____

Permit Number: _____

Contact Person: _____ Telephone #: _____

Pool Contractor: _____ License#: _____

Pool Contractor Address: _____

Date work scheduled to begin: _____

Detailed work proposed to be done: _____

Rule 64E-9.005(2)(h) states that the County Health Department shall be notified in writing any proposed resurfacing or upgrades to decking prior to commencement.

The notification shall include an itemized list of all proposed work that is to be performed, the license number of the contractor selected and shall indicate that all work will meet the requirements of paragraphs 64E-9.005(2)(a) through (g), F.A.C., outlined on back page.

There is a \$50.00 resurfacing fee payable to: Lee County Health Department

I certify that above information is accurate to the best of my knowledge.

Signature _____ Date _____



Environmental Engineering Division
60 Danley Drive, Unit 1 • Fort Myers, FL • 33907
Phone: 239-274-2200 • Fax: 239-274-2201
www.leechd.com





Rick Scott
Governor

H. Frank Farmer, Jr., M.D., Ph.D.
State Surgeon General

**PUBLIC SWIMMING POOL RESURFACING REQUIREMENTS-CHAPTER 64E-9, FLORIDA
ADMINISTRATIVE CODE**

Resurfacing the pool interior to original non-toxic slip-resistant and smooth specifications or equivalent replacement of equipment is not considered a modification. However, the following items shall be addressed during resurfacing projects:

Rule 64E-9.005(2)(h) states that the County Health Department shall be notified in writing of any proposed pool resurfacing or upgrades to decking prior to commencement. The notification shall include an itemized list of all proposed work that is to be performed, the license number of the contractor selected and shall indicate that all work will meet the requirements of paragraphs 64E-9.005(2)(a) through (g), F.A.C., outlined below.

A. The lip of the gutter must be leveled to within 1/4 inch between the highest and lowest point and the downward slope from the lip to the drain must be maintained as originally designed or increased, but shall not exceed new construction standards.

B. Tile step markings must be installed meeting the requirements of subparagraph 64E-9.006(1)(d)3., F.A.C:

64E-9.006(1)(d)3: Stairs – Stairs shall have a minimum tread width of 10 inches and a maximum width of 48 inches for a minimum tread length of 24 inches and a maximum riser height of 10 inches. Treads and risers between the top and bottom treads shall be uniform to within 1/2 inch in width and height. The riser heights shall be measured at the marked step edges and the differences in elevation shall be considered the riser heights. The front 3/4 to 2 inches of the tread and the top 2 inches of the riser shall be tile, dark in color, contrasting with the interior of the pool. **Tile shall be slip resistant.** Bullnose tile may be used when the 3/4ths inch segment is placed on the tread or horizontal surface and the 2 inch segment is placed on the riser or vertical surface.

C. Where applicable the slope break marking must be installed meeting the requirements of subparagraph 64E-9.006(1)(c)2.b., F.A.C., and the safety line must be installed two feet before the marking.

64E-9.006(1)(c)2.b: Pool Floor Slope Transition - Any transition in floor slope shall occur at a minimum of five feet of water depth. A slope transition must have a 2 to 6 inch wide dark contrasting tile marking across the bottom and must extend up both sides of the pool at the transition point. The marking shall be continuous except for necessary grouting. A slope transition must have a safety line mounted by use of recessed cup anchors, two feet before the contrasting marking, towards the shallow end. The safety line shall have visible floats at maximum seven foot intervals.

D. Depth markers and NO DIVING markers must be installed in accordance with subparagraph 64E-9.006(1)(c)3., F.A.C.

64E-9.006(1)(c)3: Depths and Markings – The minimum water depth shall be three feet in shallow areas and four feet in deep areas.

a. Permanent depth markings followed by the appropriate full or abbreviated words "FEET", "FT" or "INCHES", "IN", shall be installed in minimum four inch high numbers and letters on a contrasting background. Depth markers shall indicate the actual pool depth, within three inches, at normal operating water level when measured three feet from the pool wall. Symmetrical pool designs with the deep point at the center may be allowed provided a dual marking system is used which indicates the depth at the wall and at the deep point.

b. At a minimum, the markings shall be located on both sides of the pool at the shallow end, slope break, deep end wall and deep point (if located more than five feet from the deep end wall). Depth markings shall be legible from inside the pool and also from the pool deck. The maximum perimeter distance between depth markings is 25 feet. Pool size and geometry may necessitate additional depth marking placements about all sides of the pool to meet this requirement. When a curb is provided, the depth markings shall be installed on the inside and outside or top of the pool curb. When a pool curb is not provided, the depth markings shall be located on the inside vertical wall at or above the water level and on the edge of the deck within 2 feet of the pool water. When open type gutter designs are utilized, depth markers shall be located on the back of the gutter wall.

c. When deck level perimeter overflow systems are utilized, additional depth marking signs shall be posted nearby or placed on adjacent fencing or walls and the size shall be increased so they are recognizable from inside the swimming pool. Alternatively tile depth markers may be placed at the top of the pool wall just under the water level. Depth markers placed on the pool deck shall be within 3 feet of the water.

d. Those areas of the pool that are not part of an approved diving bowl shall have dark contrasting tile four inch high "NO DIVING" markings installed along the perimeter of the pool on the top of the pool curb or deck within two feet of the pool water with a maximum perimeter distance of 25 feet between markings. A 6-inch tile with a 4-inch or larger red, international "NO DIVING" symbol may be substituted for the "NO DIVING" markings.

e. All markings shall be tile, except that pools constructed of fiberglass, thermoplastic or stainless steel may substitute other type markings when it can be shown that said markings are permanent and will not fade over time. This exemption does not extend to concrete pools that are coated with fiberglass. Tile alternative examples include stone or manufactured plaques with engraved or sandblasted numbers and characters with permanent paint. Permanent appliques may be used for fiberglass, thermoplastic or stainless steel pools. All markings installed on horizontal surfaces shall have a slip resistant finish. Markings shall be flush with the surrounding area where placed and recessed if necessary to provide a smooth finish that will avoid creation of an injury hazard to bathers. Pools that are not conducive to tile can employ other equivalent markings as stated above.

E. The pool ladder must have a three to six inch clearance from the pool wall.

F. Should resurfacing works affect the step riser heights, no riser shall exceed 12 inches and the intermediate risers shall be made uniform.

G. When fiberglass is used to resurface a pool any existing tile shall not be covered by the fiberglass finish.

H. Upon completion of the work the licensed contractor shall provide the County Health Department a letter bearing their license number which certifies that the work was completed in accordance with paragraphs 64E-9.005(2)(a) through (h), F.A.C.

The painting of pools shall not be considered a modification provided the following conditions are met:

A. Only paints designated by the manufacturer as pool paints are used.

B. All step stripes, slope break markers and safety line, and depth and NO DIVING markings shall be provided to comply with the above resurfacing requirements, 64E-9.005(2), F.A.C.



Environmental Engineering Division
60 Danley Drive, Unit 1 • Fort Myers, FL • 33907
Phone: 239-274-2200 • Fax: 239-274-2201
www.leechd.com

